

# J E T<sup>®</sup>

## 10" DELUXE XACTA<sup>®</sup> SAW

From our shop to yours - the new Deluxe Xacta<sup>®</sup> Saw was designed for success. The quick release riving knife and push button arbor lock make operation safer and trouble-free. A fully shrouded blade connected to the 4" dust port makes dust collection a breeze. The built-in sealed storage drawer keeps often used tools or accessories close at hand, and dust free.



*Quick release riving knife*



*Poly-V belt drive system and arbor lock*



The Quick Change Riving Knife system incorporates maximum safety with ease of functionality. It's tool-less design makes blade change easy and fast.

## 10" DELUXE XACTA® SAW

- Exclusive 30" or 50" rip capacities Commercial XACTA® Fence II with T-square design
- Quick release riving knife greatly reduces binding/kickback risk
- Independent leaf blade guard protects operator from blade
- Push button arbor lock (patent pending) for rapid blade change
- Shrouded Blade increases dust collection efficiency
- Standard 11" left and right cast iron extension wings provides the largest table surface in its class
- Poly-V drive belt system delivers efficient, quiet operation
- Rail-mounted magnetic switch is easy to reach and provides overload protection
- Enclosed cabinet with built-in sealed storage drawer
- Hinged motor cover on cabinet gives quick access to the motor and belts
- Deluxe miter gauge with adjustable positive stops and large soft grip handles provides large crosscutting capacity and accurate miters

STOCK NUMBER	708674PK
Model Number	JTAS-10XL30-1DX
Net Weight (lbs.)	490
Blade Diameter (in.)	10
Arbor Diameter (in.)	5/8
Arbor Speed (RPM)	4300
Maximum Depth of Cut (in.)	3
Maximum Depth of Cut at 45 Degrees (in.)	2-1/8
Maximum Rip Right of Blade (in.)	30 or 50
Maximum Rip Left of Blade (in.)	13
Table in Front of Saw Blade at Maximum Depth of Cut (in.)	10
Maximum Width of Dado (in.)	13/16
Maximum Diameter of Dado (in.)	8
Table Height (in.)	34
Table Size with Standard Extension (L x W/in.)	29 x 42
Table Size without Extension (L x W/in.)	29 x 20
Dust Port Diameter (OD/in.)	4
Motor Amps	14.5
Motor HP	3HP or 5HP
Motor Phase	1Ph or 3Ph
Motor Voltage	230/460V (Prewired 230V) *Requires additional parts for 460V operation.

708674PK	708675PK	708676PK	708677PK	708680PK	708681PK
10" DELUXE XACTA®SAW 3HP, 1PH, 30" RIP	10" DELUXE XACTA®SAW 3HP, 1PH, 50" RIP	10" DELUXE XACTA®SAW 5HP, 1PH, 30" RIP	10" DELUXE XACTA®SAW 5HP, 1PH, 50" RIP	10" DELUXE XACTA®SAW 5HP, 3PH, 30" RIP	10" DELUXE XACTA®SAW 5HP, 3PH, 50" RIP

